

Technical Bulletin

Graffiti Off

Low Hazard Graffiti Remover

Product Description:

GRAFFITI OFF is a unique and powerful liquid compound specially formulated for the rapid and effective removal of spray paint graffiti from brick, concrete, steel and other materials of construction. GRAFFITI OFF contains special surfactants, solvents and wetting agents, to ensure a most effective clean and the removal of most common types of aerosol spray paints. GRAFFITI OFF is designed for use on brick and concrete, it is not recommended for use on other painted surfaces, as its powerful action may remove substrate paints. Castle can offer alternative systems for painted substrate application. With a combination of solvent and surfactant stripping agents, the unique formulation of GRAFFITI OFF really minimises the time taken for graffiti clean up. GRAFFITI OFF is a ready to use product, eliminating the necessity for dilution, therefore avoiding the possibility of wrong concentration and consequent poor cleaning results.

Application:

GRAFFITI OFF is best applied by spraying or brushing onto surfaces to be cleaned, leave for a minimum of five minutes, and then rinse off with clean water. For small areas a mains pressure water hose will be adequate, but preferably the use of a water pressure washer is recommended.

As GRAFFITI OFF is a combination of solvent and detergents, operators should wear protective clothing, rubber gloves and safety glasses at all times. DO NOT take internally. In case of contact, immediately wash skin or eyes with plenty of water for at least 15 minutes. For eyes, consult a doctor. GRAFFITI OFF is classed as Hazardous material, but not a Dangerous Good and non-flammable. GRAFFITI OFF is best stored in cool dark areas away from heat and ignition sources. Always use original containers.

APPEARANCE Light tan clear liquid

FLASHPOINT 91°C

pH Solvent product N/A

SPECIFIC GRAVITY 1.02 – 1.03

CORROSION Non corrosive to most metals.

SHelf Life: As a quality assured manufacturer, Castle Chemicals has a stringent Quality assurance programme. As part of this regime, the label on this product shows a batch number and date of manufacture. This product has a shelf life of 24 months from the label printed date of manufacture. This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Castle Chemicals assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of material.

Page 1 of 1